



MODEL	1102	1103	1105	1107	1110	1115	1120	1125	1130
Power kVA	2	3,5	5	7,5	10	15	20	25	30
<b>INPUT</b>									
Input Voltage	90 V ~ 270 V Ac								
Operation Frequency	47 ~ 65 Hz								
<b>REGULATOR OUTPUT</b>									
Output Voltage	220V Ac, ±3%								
Overload	200% of Load for 10 Sec.								
Output Protection	Protection Overload, Over/Under Voltage, Over Heat								
Working Principle	Automatic								
Transfer Time	1 Sec								
<b>GENERAL</b>									
Cooling System	Smart Fan System								
Indication	7 segment display								
Total Harmonic Distortion	Yes								
Total Efficiency	> 97%								
Protection Level	IP 25								
<b>ENVIRONMENTAL</b>									
Working Temperature	-10 °C , 80 °C								
Storage Temperature	-25 °C / +60 °C								
Relative Humidity	< % 90, DIN ( 40040 )								
Working Altitude	< 2000 m.								
Acoustic Level	< 50 dB ( 1 metersquare )								
Documents	CE // TÜV Austria Hellas (ISO 9001)								
<b>DIMENSIONS (cm)</b>									
Height	26,5	26,5	26,5	28	31,5	32,5	37	32	32
Width	25,5	25,5	42	27,5	45,5	48,5	50,3	55,3	55,3
Depth	27	27	19	29	22,5	25,5	29,5	29,5	29,5
Weight (kg)	14	15	20	25	30	44	56,2	66	70



Merkez Mah. Çınar Cad. Sedir Sok. No.:1 Kat: 2  
 Yenibosna - Bahçelievler / İstanbul / TÜRKİYE  
 Tel : +90 212 639 22 73 • 639 21 02 • 639 06 75  
 Faks : +90 212 654 90 54 • Firma Gsm: +90 533 481 06 52  
[info@deltaregulator.com](mailto:info@deltaregulator.com) • [www.deltaregulator.com](http://www.deltaregulator.com)

