

TECHNICAL DATA

Fluke 325 True RMS Clamp Meter



Key features

- True-rms AC/DC current, voltage, temperature, frequency
- Clamp meter, test leads, K-type thermocouple and soft case
- Versatile tool performs most front-line measurement tasks

Product overview: Fluke 325 True RMS Clamp Meter

Troubleshoot problems safely and accurately

The Fluke 325 True-rms Clamp Meter is a reliable, versatile troubleshooting tool for commercial and residential electricians. Featuring a slim design for easy transport and use, and a large display for efficient troubleshooting. In addition to true-rms AC current and voltage on non-linear loads, the 325 measures:

- DC current
- DC voltage
- Temperature
- Frequency

You'll carry fewer tools in your bag and get more work done.

Covers most problems you see day-in, day-out

The 325 gives you a strong combination of measurement functions, in a tool that is reliable, easy-to-use and affordable. This

clamp meter offers True-rms AC voltage and current measurements on non-linear signals. Paired with the CAT III 600 V, CAT IV 300 V safety rating the clamp meter can also measure:

- Measures AC/DC current up to 400 A through jaw
- AC/DC voltage to 600 V using test leads
- Measures frequency from 5 Hz to 500 Hz; resistance to 40 kΩ
- Measures temperature from -10 °C to 400 °C with included K-type thermocouple
- Min/Max function records important values

Comes with a two-year warranty

Specifications: Fluke 325 True RMS Clamp Meter

| Specifications | | |
|----------------|----------|---|
| AC current | Range | 40.00 A / 400.0 A |
| | Accuracy | 2% ± 5 digits (45 Hz to 65 Hz) 2.5% ± 5 digits (65 Hz to 400 Hz) |
| DC current | Range | 40.00 A / 400.0 A |
| | Accuracy | 2% ± 5 digits |
| AC voltage | Range | 600.0 V |
| | Accuracy | 1.5% ± 5 digits |
| DC voltage | Range | 600.0 V |
| | Accuracy | 1.0% ± 5 digits |
| Resistance | Range | 400.0 Ω / 4000 Ω / 40.00 kΩ |
| | Accuracy | 1.0% ± 5 digits |

| | | |
|---------------------|--|-----------------|
| Continuity | ≤ 30 Ω | |
| Capacitance | 0 to 100.0 μF / 100μF to 1000 μF | |
| Frequency | 5.0 Hz to 500.0 Hz | |
| AC response | True-RMS | |
| Backlight | Yes | |
| Data hold | Yes | |
| Contact temperature | -10.0°C to 400.0°C (14.0°F to 752.0°F) | |
| Min/Max | Yes | |
| Size | H x W x D (mm) | 207 x 75 x 34 |
| | Max wire diameter | 30 mm (600 MCM) |
| | Weight | 283 g |
| Category rating | CAT III 600 V CAT IV 300 V | |
| Warranty | Two-year | |

Ordering information



Fluke 325

Fluke 325 True-RMS Clamp Meter

Includes:

- Fluke 325 True-RMS Clamp Meter
- TL75 Test Leads
- Type K Thermocouple
- Two AAA Batteries (Installed)
- Soft Case

Optional accessories

Description

Fluke TL223 SureGrip™ Electrical Test Lead Set

Includes 3 test lead accessories in an all-in-one set. Ideal starter kit for electrical applications.

Fluke C43 Soft Carrying Case

Zippered carrying case with durable polyester exterior.

Fluke CAMO-37 Camouflage Carrying Case

Get the right case for your Fluke tools. The CAMO-37 camouflage carrying case is a zippered carrying case with durable high quality polyester exterior. It has a belt loop and an inner pocket to store test leads or small accessories. It is available in a trendy camouflage design with a 1 year warranty.



Fluke. *Keeping your world up and running.*®

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Canada (800) 36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com

©2024 Fluke Corporation.
Specifications subject to change without notice.
09/2024

**Modification of this document is not permitted
without written permission from Fluke Corporation.**